# IPC-SP2E097

Fanless Embedded PC Intel® Celeron® J3455 / N3350 / Atom® x5-E3940 Processor



#### **Features**







- Optional support for low temperature environments
- Powered by highly cost performance SoC
- Storage support both 2.5" & mSATA type
- Support DC In 12V, 19V, 24V wide voltage power input

### **Specifications**

System	
The second secon	
CPU Support	Intel® Celeron® J3455: 10w, 4C, 1.5GHz
	Intel® Celeron® N3350: 6w, 2C, 1.1GHz
	Intel® Atom® x5 E3940: 10w, 4C, 1.6GHz
Memory Support	1 x SO-DIMM socket, supporting 1600/1866MHz
	DDR3L memory up to 8G (non-ECC)
API/SW/FW	Watchdog / HW monitor / fTPM
Storage Support	2.5" 7 mm SATAIII HDD or SSD drive space
Power Input	Wide-ranged voltage DC In 12V and 19, 24V
Power Adapter	60W adapter w/ lockable 3 pin terminal block
Operating System	Windows 10 64bit / Ubuntu17.04 (kernel:4.4)
Expansion Slots	1 x full-sized mSATA slot (with USB signal)
	1 x full-sized mPCle slot (with USB signal)
System Weight	2 kg
Dimensions	217.5 x 46.6 x 140.6 mm (W x H x D) (without Rubber Foot)
Certifications	FCC / CE

### I/O Ports (Front side)

USB	2 x USB 2.0
Serial Ports	COM 1: RS232 COM 2: RS232/422/485 (selectable under BIOS) COM 3 & COM 4: RS-232 with RI/5V/12V selectable by jumper
LAN (optional)	2 x LANs, supports - Optional, must remove 2 x USB & COM 1 & COM 4 - Support PSE (option)
Antenna Hole	4 x antenna holes (supports up to 4 antenna)

#### I/O Ports (Rear side)

.,	
Power Input	3 pin DC In terminal block (lockable), supporting 12V and 19V, 24V
Power On/Off	1 x Power Button, 1 x Extended Power Connector
LED	1 x Power LED
Display	1 x VGA, 1 x HDMI1.4a
LAN	2 x LANs (supports Wake-On-LAN) LAN 1: Intel® I210IT LAN 2: Intel® I210IT
Audio	1 x Line Out
USB	4 x USB 3.0

# **System Front View & Rear View** Normal\_Front USB 2.0 DIO / COM 4 COM 3 COM 2 COM 1 LAN\_Front LAN 3 LAN 4 DIO / COM 2 COM 3 СОМ 3 PoE\_Front LAN 3 LAN 4 DIO / COM 2 Power Button DC In VGA LAN 2 HDMI USB 3.0 Rear View Power LED Remote Switch LAN 1 Line Out

## **Environment**

Operating Temp. Celeron J3455: 0°C~40°C (32°F~104°F) (Ambient with airflow) Celeron N3350: 0°C~40°C (32°F~104°F) Atom E3940: -40°C~60°C (-40°F~140°F)

Storage Temp. -40°C~85°C (-40°F~185°F)

Humidity 20%~90%

<sup>\*</sup> All information contained in this document is subject to change without prior notice. Please log on www.antcomputer.com to acquire latest information. For detail mechanics drawing, please contact our sales.